

Product Specifications

style name	grain
style number	0364V
construction	luxury vinyl plank with In*Step locking system
class / ASTM F1700	class III printed film vinyl plank, type A (smooth), type B (embossed)
nominal dimensions	7 in wide x 48 in long
wearlayer thickness	20 mil or 0.020" (0.5 mm)
overall thickness	4 mm or .156 in
actual size / ASTM F536	width: 7.28 in or 18.5 cm, length: 47.72 in or 121.2 cm
backing class	commercial grade
finish	ExoGuard™ quartz-enhanced urethane
edge profile	micro bevel
added antimicrobial	yes, FlorSept™
installation recommended	floating
adhesive	none required, not recommended

Packaging

square feet per carton	24.13 sf
pieces per carton	10 pcs
weight per carton	33.72 lbs

Testing

IIC sound rating ASTM E492	greater than 55 when tested over 6" concrete with ceiling plenum and approved underlayment
slip resistance ASTM D2047	ADA compliant
static load ASTM F970	500 psi
flexibility ASTM F137	passes
resistance to heat ASTM F1514	passes
resistance to light ASTM F1515	passes
resistance to chemicals ASTM F925	passes
radiant panel ASTM E648	class I
nbs smoke ASTM E662	less than 450

Warranty

10 year limited commercial wear warranty.
Please visit www.shawhardsurface.com for the most current warranty information.

Environmental

Indoor Air Quality FloorScore® certified



Specifications are subject to nominal manufacturing variance.
Material supply and/or manufacturing processes may necessitate changes without notice.