shaw hard surface[®]

Pigment

Product Specifications

style namepigmentstyle number0365V

construction luxury vinyl plank with In*Step locking system

class / ASTM F1700 class III printed film vinyl plank, type A (smooth), type B (embossed)

nominal dimensions7 in wide x 48 in longwearlayer thickness overall20 mil or 0.020" (0.5 mm)

thickness 4 mm or .156 in

actual size / ASTM F536 width: 7.28 in or 18.5 cm, length: 47.72 in or 121.2 cm

backing class commercial grade

finish ExoGuard™ quartz-enhanced urethane

 $\begin{array}{ll} \text{edge profile} & \text{micro bevel} \\ \text{added antimicrobial} & \text{yes, FlorSept}^{\text{TM}} \end{array}$

installation recommended floating

adhesive none required, not recommended

Packaging

square feet per carton24.13 sfpieces per carton10 pcsweight per carton33.72 lbs

Testing

IIC sound rating ASTM E492 greater than 55 when tested over 6" concrete with ceiling plenum and

approved underlayment

slip resistance ASTM D2047 ADA compliant

static load ASTM F970 500 psi
flexibility ASTM F137 passes
resistance to heat ASTM F1514 passes
resistance to light ASTM F1515 passes
resistance to chemicals ASTM F925 passes
radiant panel ASTM E648 class I

nbs smoke ASTM E662 less than 450

Warranty

10 year limited commercial wear warranty.

Please visit www.shawhardsurface.com for the most current warranty information.

Environmental

Indoor Air Quality FloorScore® certified

